

3/19/4

DIALOG(R)File 347:JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

04750248 **Image available**
SEAL UNIT OF SHAFT SEALING DEVICE

PUB. NO.: 07-042848 [JP 7042848 A]
PUBLISHED: February 10, 1995 (19950210)
INVENTOR(s): ISHIBASHI SUSUMU
APPLICANT(s): MITSUBISHI HEAVY IND LTD [000620] (A Japanese Company or
 Corporation), JP (Japan)
APPL. NO.: 05-194621 [JP 93194621]
FILED: August 05, 1993 (19930805)
INTL CLASS: [6] F16J-015/32
JAPIO CLASS: 22.1 (MACHINERY -- Machine Elements); 43.1 (ELECTRIC POWER --
 Generation)

ABSTRACT

PURPOSE: To shorten the time for seal unit installation by assembling a seal unit through fixing of a shaft sleeve to a seal casing with a thrust support plate and end-face seal collar interposed, and fitting the shaft sleeve of the unit on a rotary shaft.

CONSTITUTION: A shaft sleeve 11 is inserted in a seal casing 8, and a thrust support plate for the shaft sleeve 11 is mounted on a thrust collar 15 using a bolt 17 so that the two 8, 11 are consolidated. Therein a spacer 14 is interposed between the thrust collar 15 and thrust support plate 12 so that a non- contact gap Δ is reserved in between. Radial lip seals 18, 19 retained in the seal casing 8 are contacted with the radial seal surface S(sub 1) of the shaft sleeve 11, and the chamber 21 between the seals 18, 19 is filled with grease G to make leak check and a seal unit H is assembled. A rotary shaft is inserted in the shaft sleeve 11 of this seal unit H, which is secured to a housing using bolts.

C:\Program Files\Dialog\DialogLink\Graphics\34.bmp

